

Cleanrex RM

DESCRIPTION:

Cleanrex RM is a low-foaming washing and degreasing agent. Micro-emulsion concentrate based on surfactants, fatty acid esters, wetting agents, water softeners. It is an excellent alternative to strongly alkaline cleaning agents and preparations based on hydrocarbon solvents. Cleanrex RM is non-flammable, has a delicate smell, slightly alkaline pH and is water-dilutable. This preparation is inert to varnish coatings, plastics and non-ferrous metals. It does not corrode metals. It does not contain carcinogenic and mutagenic ingredients.

APPLICATION:

Removal of heavy industrial contamination, stains from oil, grease, anti-corrosion preparations and other hard-to-wash dirt, e.g. asphalt, tar, adhesives, etc.

Cleanrex RM is used to clean metal and plastic parts, machine parts, pumps, oil mixers, industrial floors and the road transport fleet.

Dane Techniczne		
Density 20°C	DIN 51757-4	1,02 g/cm³
pH	-----	9
Form at 20°C		transparent liquid
Pour point	ISO 3016	< 0°C
Flash point	-----	not flammable
Min. application temperature	-----	5°C
Water solubility	-----	unlimited
Cloud point	-----	75°C

DIRECTIONS FOR USE

It can be used in the form of a concentrate or after dilution with water. The dilution ratio depends on the type and degree of soiling. The maximum recommended dilution is 1:30 (approx. 3% solution)

Cleanrex RM can be used at room temperature, but higher temperatures increase cleaning efficiency and reduce foaming. The maximum application temperature for the concentrate is 73° C, for a 1: 5 solution with water 48° C. Cleanrex RM is a completely non-flammable preparation, which makes it safe in many industrial applications

PACKAGING

20l canister

5l canister

STORAGE

The product should be stored in original packaging at a temperature of + 0°C to + 50°C.

OTHER

The product does not contain petroleum distillates, chlorinated solvents and butyl fractions. It is biodegradable.